

CONFIDENTIAL

25X1

December 4, 1961

12/7/61

file:
Mod 1 Inc

Dear Sir:

Enclosed are the copies of the "advertising" pieces for the
(Models 1, 2, and 3 Air-Fed Incinerators) that you left with us for our
 comments. Glen and I have reviewed these and have suggested some changes,
 which are indicated in pencil on the enclosed.

If you have any questions about our suggested changes, please
 do not hesitate to call.

Sincerely,

25X1

ABW:mlm

In Duplicate

Enclosures

ORIGINAL CL BY 23 59 79
☐ DECL ☒ REVW ON 08/07/2010
 EXT BYND 6 YRS BY SAME
 REASON 3 d (3)

008632

DOC	102	REV DATE	8 July 80	BY	057447
ORIG COMP	056	OPI	56	TYPE	01
ORIG CLASS	4	PAGES	2	REV CLASS	C
JUST	22	NEXT REV	2016	AUTH	HR 70-2

CONFIDENTIAL

+124

Mod 1 Inc.

CONFIDENTIAL

MODEL I AIR-FED INCINERATOR

The Model I Air-Fed Incinerator is provided for those facilities requiring the capability of emergency destruction of classified documents at a maximum rate. Additionally this unit may be used for daily or weekly scheduled burn periods which will provide a maximum security capability not heretofore available. The incinerator will destroy all paper or paper products including film, negatives and those products of combustible nature manufactured of cellulose base materials. Given below is the technical data characteristics and requirements for the installation and operation of this incinerator.

Technical Data

Capacity: ²⁰⁰⁻⁴⁵⁰ ~~200-240~~ pounds of material per hour.

Electrical Requirement: 3 phase, 60 or 50 cycle, 208, 220/380 or 208, 220/440 voltage is essential.

Space Requirement: Physical: 28 square feet (7 feet long, 4 feet depth). Functional: 4 inches should be added on each end and in the back for air space and the front should be cleared for loading and maintenance. Ceiling, minimum 8 feet 6 inches. Shipped in 7 pieces for individual facility assembly. Common tools are required for assembly and 4 to 5 personnel available to assist in lifting and handling.

Description: 42 inches outside diameter, 80 inches in height, requiring exhaust stacking to outside. Stack configuration (to be built at facility), welded, stainless steel construction with a minimum of 200 square inches in cross sectional area.

Stock Order Number

3/4540-H00-4404

CONFIDENTIAL